

Documentation

Installation Guide

Application

Hardware debug
Software debug
Flash Programming

Warranty: 1 year from date of purchase for emulator and power supply

Part #:701515

SPI515 JTAG Emulator (supports low voltage DSPs)



SPI515 Adjustable Voltage, Parallel Port JTAG Emulator

Hardware Features

- Supports Texas Instrument's Digital Signal Processors and Microcontrollers with **JTAG** interface (C2xx, C24x, F240x, F28xxx, VC33, C4x, C5x, C54xx, C55xx, C6xxx, C64xx, C674x, TMS470, OMAP™, DaVinci™)
- JTAG Variable Voltage interface senses target power and adjusts input and output levels (+1 to +5 V)
- Advanced emulation controller provides high performance
- Portable operation, no adapter card required, communicates to host via standard parallel port, LPT1, (SPP8, EPP, ECP up) To 1 Mbyte/sec transfer rate)

Software Features

- Compatible with the Full License of Code Composer Studio versions 3.x and v4 from Texas Instruments
- Compatible with Windows 2000, XP, and Vista
- Supports Spectrum Digital's flash programming utilities

What's Included

- SPI515 JTAG Emulator
- +5 Volt power supply
- Parallel port cable
- CD-ROM with drivers

Do You Need ?

- Code Composer Studio
- DSP target board (EVMs, DSKs, eZdsp)
- 14-20 pin Adapter

- Six LEDs provide operational status
- Power by supplied AC adapter

© 2002-2013 Spectrum Digital, Inc. All Rights Reserved.
