

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:

CONTACT MATERIAL: BRASS

SURFACE PLATING:

SILVER PLATING: $\geq 2\mu\text{m}$ CONTACT RESISTANCE: $\leq 0.5\text{m}\Omega$ WIRE RANGE: 25 mm²

OPERATION TEMPERATURE: -40~+125°C

注释:

1. 技术参数:

公针材料: 黄铜

表面电镀:

镀银: $\geq 2\mu\text{m}$ 接触电阻: $\leq 0.5\text{m}\Omega$ 接线范围: 25 mm²

工作温度: -40~+125°C

T2060002025-000	CHF-25	CHF-25, SILVER PLATING HMN-001母针 25mm ² , 镀银	25	19
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE (mm ²) 线规 (mm ²)	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang		
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu	NAME CHF-25 HM SOCKET CONTACT	
0 PLC ±-		PRODUCT SPEC 108-137057	SIZE	
1 PLC ±-		APPLICATION SPEC 114-137057	CAGE CODE	
2 PLC ±-		WEIGHT	DRAWING NO	
3 PLC ±-		Customer Drawing	RESTRICTED TO	
4 PLC ±-			A300779	
ANGLES ±-			C-T2060002025000	
FINISH			SCALE	
-			2:1	
-			SHEET	
			1 OF 1	
			REV	
			A1	

1470-19 (3/13)