

Specification Sheet

Part Number: 596-00368



| Article Number | 596-00368 |
|---------------------|--|
| Туре | IOCOD |
| Color | Red (RD) |
| Features & Benefits | Made with UV stable inks and materials for durability and weather resistance. The labels are supplied with aggressive adhesive to ensure long life. Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. |
| Quantity Per | reel |

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

| Short Description | Solar Label, WARNING INVERTER OUTPUTOVERCURRENT DEVICE, 4.12" x .75", VL, Red, 50/roll |
|--------------------------------|--|
| Global Part Name | IOCOD-V-RD |
| Technical Description | Pre-Printed Solar Label, 4.12" X .75", WARNING - INVERTER OUTPUT CONNECTION, Red |
| | |
| Width W (Imperial) | 4.12 |
| Width W (Metric) | 104.6 |
| Height H (Imperial) | 0.75 |
| Height H (Metric) | 19.05 |
| | |
| Material | Vincel |
| Material | Vinyl |
| Material Shortcut | V |
| Adhesive | Acrylic |
| Halogen free | Yes |
| Adhesive Operating Temperature | -40°F to +174°F (-40°C to +79°C) |
| Operating Temperature (Metric) | -40°F to +174°F (-40°C to +79°C) |
| ROHS Complaint | Yes |

| | 02 000 N2 02 0 N |
|----------------------------|------------------|
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| | |
| Package Quantity(Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3919905060 |

UL 969 NEC2011 IFC 2012

Certification/Specification WEB

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2018} HellermannTyton. All rights reserved.